

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,

68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3,Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876



Email: info@federalpaint.com.my

Website: federalpaint.com.my

TECHNICAL DATA SHEET NO: FS19

FELTEC ROAD MARKING PAINT

Reflective & Non- Reflective Road Marking Paint

PRODUCT DESCRIPTION	Feltec Road Marking Paint is a quick drying synthetic paint with exceptional durability. It is specially designed to maximize abrasion and chemical resistance.
TECHNICAL INFORMATION Colour Finish Flash Point	White (R & NR), Black (NR) and Yellow (R & NR) Reflective (R) and Non-Reflective (NR) About 23°C
RECOMMENDED USE	Feltec Road Marking Paint is specially designed for the marking of road, car park, factories, schools, etc.
PRODUCT DATA Recommended Dry film Thickness Drying times Recoat Theoretical coverage Volume Solids	30 ~ 40 microns Touch Dry : 20 minutes Hard Dry : 1 hour Min : 1 hour 9 - 10 m ² / liter per coat Approx. 50 ~ 60%
APPLICATION DATA Application Method Mixing Ratio (by volume) Thinner/cleaner Surface Preparation	Brush/ Roller/Spray Gun The paint is ready for use after proper stirring. If thinning is required, add 5% of Federal General Thinner MO-475 for easy application. Federal General Thinner MO-475 Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.
SHIPPING, STORAGE & PACKAGING Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 5 liters
SAFETY PRECAUTION	<ul style="list-style-type: none">* This product is flammable. Keep away from sources of ignition. Keep container tightly and keep out of reach of children.* Wear suitable personal protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe or inhale mist.* Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.

FP02@03/13