

FEDERAL PAINT MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,
68000 Ampang, Selangor.
Tel : 03-4292 4684 Fax : 03-4291 5303
Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.
Tel : 03-8737 8826 Fax : 03-8737 8876



Email: info@federalpaint.com.my
Website: federalpaint.com.my

TECHNICAL DATA SHEET NO : MS2

SUPER-10

Alkyd Gloss Finish

PRODUCT DESCRIPTION	SUPER-10 is a alkyd gloss finish, which is formulated for interior and exterior application for metal and wood surfaces. It is easy to apply and it forms a smooth, tough paint film, which has excellent gloss, fungus resistance and durability.
TECHNICAL INFORMATION Colour Specific Gravity Finish Flash Point	Refer to Super-10 colour card Approximately 0.9 ~ 1.2 High gloss About 35°C
RECOMMENDED USE	SUPER-10 is suitable for use on all types of interior and exterior wood & properly primed metal.
PRODUCT DATA Recommended Dry film Thickness Drying Time (at 27°C) Recoating Interval Theoretical Coverage	30 ~ 35 microns Touch Dry : 4hours Hard Dry : 18hours Overnight 10 ~ 12 m ² / liter per coat When computing actual coverage, allow for application losses, surface irregularities etc.
APPLICATION DATA Application Method Thinner/cleaner Surface Preparation	Brush/ Roller/Spray Royal Thinner 464 Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.
SHIPPING, STORAGE & PACKAGING Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 1 & 5liters.
SAFETY PRECAUTION	<ul style="list-style-type: none">* This product is flammable. Keep away from sources of ignition. Keep container tightly and keep out of reach of children.* Wear suitable personal protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe or inhale mist.* Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.