

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,
68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876



Email: info@federalpaint.com.my

Website: www.federalpaint.com.my

Technical Data Sheet No: FW10

FELTEC ROOF GUARD Exterior Paint for Rooftiles

PRODUCT DESCRIPTION	Feltec Roof Guard is a high quality mid sheen water-borne acrylic coating, which is formulated for old and new roofs such as cement fibre sheets and unglazed roof tiles. Feltec Roof Guard is pigmented with light stable colorant that provides a smooth and highly decorative finishing with good durability and weathering properties against ultraviolet degradation and fungus growth.
TECHNICAL INFORMATION Colour Finish Flash Point	Refer to color card Mild sheen Non-Flamable
RECOMMENDED USE	Feltec Roof Guard is used as protective/decorative coating over old and new roof tiles.
PRODUCT DATA Recommended Dry film Thickness Drying times Recoat Theoretical coverage	30 ~ 50 microns Touch Dry : 30 minutes Min : 2 hours Approx 10 m ² /lit. When computing actual coverage, allow for application losses, surface irregularities etc.
APPLICATION DATA Application Method Mixing Ratio (by volume) Thinner/cleaner Surface Preparation	Brush/ Roller/Spray The paint is ready for use after proper stirring. If thinning is required, water may be added up to a max 5%. Water Surfaces must be dry, clean and free from any loose material to ensure good adhesion. Remove all loose or defective paint or powdery residues by thorough brushing and scrapping. On badly affected areas or where lichen is present, the use of highy pressure water-hosing may be necessary to remove all organic growth complately. Treat any areas affected by mould, lichens, algae and moss with Feltec Fungicial Wash. DO NOT use Hypoclorite Wash before or after fungicial wash as it oxidises the active ingredient and makes it ineffective. Make good minor cracks. Use sand and cement mix for larger holes and cracks. Allow to dry before applying primer/sealer. Do not apply paint during wet weather.
SHIPPING, STORAGE & PACKAGING Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 5 liters
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.