

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang,
68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876



Email: info@federalpaint.com.my

Website: federalpaint.com.my

Technical Data Sheet No: FS9

FELTEC TIMBER GUARD

Exterior Varnish for Wood & Timber Surfaces

PRODUCT DESCRIPTION	FELTEC TIMBER GUARD is a transparent colour varnish formulated for exterior application on soft and hard woods.
TECHNICAL INFORMATION	: Easy in application. : Glossy : Excellent flow : Fast dry. : Durability.
RECOMMENDED USE	FELTEC TIMBER GUARD is used on soft and hard wood, e.g. parquet floors, panelling, cane or wood furniture, doors and partitions
PRODUCT DATA Finish Color Surfaces No of coats Theoretical coverage Volume Solids Flash Point	Glossy Refer to colour Card Treated surfaces 2 or 3 coats Approx. 16 m ² /lit. Approx. 36% Approx. 35 °C
APPLICATION DATA Application Method Drying times Recoat Thinner/cleaner Surface Preparation	Brush/ Roller/Spray/Dipping. Dry touch : 4 hour 24 hours Federal General Thinner MO-464 Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.
SHIPPING, STORAGE & PACKAGING Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12months 1 & 5 liters.
SAFETY PRECAUTION	* This product is flammable. Keep away from sources of ignition. Keep container tightly and keep out of reach of children. * Wear suitable personal protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe or inhale mist. * Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.