

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang, 68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876

Email: info@federalpaint.com.my

Website: federalpaint.com.my


TECHNICAL DATA SHEET
FELTEC 1200 WALL SEALER
 Alkali- Resisting Wall Sealer
NO: FW3

PRODUCT DESCRIPTION	Feltec 1200 Wall Sealer is a high quality styrene acrylic water-based wall sealer, specially formulated for protection of finishing coats from alkali attacks, suitable for exterior and interior use.
TECHNICAL INFORMATION	Colour White only Specific Gravity Approximately 1.20 – 1.30 Finish Low sheen Flash Point Non-flammable
RECOMMENDED USE	Feltec 1200 Wall Sealer is ideally suited for new and old surfaces, porous and chalking surfaces that can be located either in the interior and exterior of the buildings e.g cement, brickwork, plaster, asbestos, etc.
PRODUCT DATA	Recommended Dry film Thickness 30 ~ 40 microns Drying times Touch Dry : 15 - 30 minutes Recoat Min : After 2 hours Theoretical coverage 10 – 12 m ² / liter per coat Volume Solids Approximately 39 %
APPLICATION DATA	Application Method Brush/ Roller/Spray Gun application. Mixing Ratio (by volume) Dilution not necessary. If required, dilute with water (maximum) 5% based on total component. Thinner/cleaner Water Surface Preparation Surfaces to be painted should be throughly dry and clean, free from grease or wax, flake, chalk and dirt.
SHIPPING, STORAGE & PACKAGING	Storage The product should be kept in a cool and well ventilated place protected from direct sunlight. Handling Handle with care. Stir well before use. Shelf life 12 months. Packing Size 5L and 18L
SAFETY PRECAUTION	<ol style="list-style-type: none"> 1. Keep container tightly closed. 2. Keep out of reach children or away from food and drink. 3. Ensure good ventilation during application and drying. 4. When applying paint, it is advisable to wear eye protection. 5. In case of contact eyes rinse with plenty of water immediately and seek medical advice. 6. Remove splashes from skin by using soap or water. 7. Paint must always be stored in a cool place. 8. When delivering paint, care must be taken. Always keep container in a secure upright. 9. Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.