

**FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)**

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang, 68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876

Email: info@federalpaint.com.my

Website: federalpaint.com.my

**TECHNICAL DATA SHEET NO: FS16****FELTEC 1011 WALL SEALER****Solvent-based Alkali Resisting Wall Sealer**

<b>PRODUCT DESCRIPTION</b>	Feltec 1011 Wall Sealer is a high quality solvent-based sealer for interior and exterior use.
<b>TECHNICAL INFORMATION</b> Colour Specific Gravity Finish Flash Point	White Approximately 1.27 Matt About 23°C
<b>RECOMMENDED USE</b>	Feltec 1011 Wall Sealer is suitable for use on both new and previously painted surfaces, such as masonry surface, brickwork, plaster, cement and asbestos
<b>PRODUCT DATA</b> Recommended Dry film Thickness Drying times Recoat Theoretical coverage	30 ~ 40 microns Touch Dry : 30 minutes Hard Dry : 1 hours Min : 1 hours 10 – 12 m <sup>2</sup> / liter per coat
<b>APPLICATION DATA</b> Application Method Mixing Ratio (by volume) Thinner/cleaner Surface Preparation	Brush/ Roller/Spray/Dipping. The paint is ready for use after proper stirring. If thinning is required, add 5% of Federal General Thinner MO-475 for easy application. Federal General Thinner MO-475 Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease etc.
<b>SHIPPING, STORAGE &amp; PACKAGING</b> Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 5 & 20 liters
<b>SAFETY PRECAUTION</b>	<ul style="list-style-type: none"> <li>* This product is flammable. Keep away from sources of ignition. Keep container tightly and keep out of reach of children.</li> <li>* Wear suitable personal protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe or inhale mist.</li> <li>* Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.</li> </ul>
<b>DISCLAIMER</b>	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.

FP03@09/23