FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office: 21, Persiaran Desa Ampang 1, Taman Sri Ampang,

68000 Ampang, Selangor.

Tel: 03-4292 4684 Fax: 03-4291 5303

Factory: Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel: 03-8737 8826 Fax: 03-8737 8876



Email: info@federalpaint.com.my Website: federalpaint.com.my

TECHNICAL DATA SHEET NO: FW1 ACRYLSHIELD

100% Acrylic Exterior Finish

ACRYLSHIELD is a premium low sheen water-borne acrylic coating, which is formulated for exterior masonry application. ACRYLSHIELD is pigmented with light stable colorant that provides a smooth and highly decorative finishing with good durability and weathering properties against ultraviolet degradation and fungus growth.
Refer to Acrylshield 100% Acrylic Exterior Finish Paint colour card Approximately 1.25 – 1.40 Low sheen Non-flammable
Acrylshield is specially formulated for use on exterior concrete and masonry surfaces.
30 ~ 40 microns Touch Dry : 15 - 30 minutes Min : 1-2 hours 11 - 13 m² / liter per coat Approximately 40~45 %
Brush/ Roller/Spray Gun The paint is ready for use after proper stirring. If thinning is required, water may be added up to a max 5%. Water Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.
The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 1L (MCS only), 5 (MCS & Ready-mixed) & 18 liters
Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.

FP02@03/13