

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang, 68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876

Email: info@federalpaint.com.my

Website: federalpaint.com.my



TECHNICAL DATA SHEET

ROYALITE

Premium Interior Matt Finish

NO: FW31

PRODUCT DESCRIPTION	Royalite is an economy matt emulsion paint based on modified acrylic binder. It can be applied on interior surfaces like walls, ceilings, soft boards and masonry surfaces.
TECHNICAL INFORMATION	Colour Refer to Royalite colour card Specific Gravity Approximately 1.40 – 1.50 Finish Matt Finish Flash Point Non-flammable
RECOMMENDED USE	Royalite is suitable for interior concrete and masonry. Not recommended for areas subject to heavy or frequent condensation.
PRODUCT DATA	Recommended Dry film Thickness 30 ~ 40 micron per coat Drying times Touch Dry : 15 - 20 minutes Recoat Min : After 2 hours Theoretical coverage 10 – 12 m ² / liter per coat Volume Solids Approximately 35 %
APPLICATION DATA	Application Method Brush/ Roller/Spray Gun application. Mixing Ratio (by volume) The paint is supplied ready for use. If thinning is required for the first coat, not more than 5% by volume of water may be added. Thinning is not recommended for subsequent coat. Thinner/cleaner Water Surface Preparation Surfaces to be painted should be throughly dry and clean, free from grease or wax, flake, chalk and dirt.
SHIPPING, STORAGE & PACKAGING	Storage The product should be kept in a cool and well ventilated place protected from direct sunlight. Handling Handle with care. Stir well before use. Shelf life 12 months. Packing Size 1L, 7L and 18L
SAFETY PRECAUTION	1. Keep container tightly closed. 2. Keep out of reach children or away from food and drink. 3. Ensure good ventilation during application and drying. 4. When applying paint, it is advisable to wear eye protection. 5. In case of contact eyes rinse with plenty of water immediately and seek medical advice. 6. Remove splashes from skin by using soap or water. 7. Paint must always be stored in a cool place. 8. When delivering paint, care must be taken. Always keep container in a secure upright. 9. Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.