

FEDERAL PAINTS MANUFACTURING (M) SDN BHD (381688-T)

Office : 21, Persiaran Desa Ampang 1, Taman Sri Ampang, 68000 Ampang, Selangor.

Tel : 03-4292 4684 Fax : 03-4291 5303

Factory : Lot 3, Batu 13, Simpang Balak, 43000 Kajang, Selangor.

Tel : 03-8737 8826 Fax : 03-8737 8876

Email: info@federalpaint.com.my

Website: federalpaint.com.my

**TECHNICAL DATA SHEET NO: FS2****GLO-10 SYNTHETIC ENAMEL****Alkyd Gloss Enamel**

PRODUCT DESCRIPTION	Glo-10 Synthetic Enamel is economical alkyd enamel with high gloss finish. It is easy to apply and it forms a smooth, tough paint film, which has excellent gloss, fungus resistance and durability.
TECHNICAL INFORMATION Colour Specific Gravity Finish Flash Point	Refer to Glo-10 colour card Approximately 0.86 ~ 1.16 High gloss About 35°C
RECOMMENDED USE	Glo-10 Synthetic Enamel is suitable for use on all types of interior and exterior wood & properly primed metal.
PRODUCT DATA Recommended Dry film Thickness Drying Time (at 27°C) Recoating Interval Theoretical Coverage	30 ~ 35 microns Touch Dry : 4hours Hard Dry : 18hours Overnight 10 ~ 12 m ² / liter per coat
APPLICATION DATA Application Method Mixing Ratio (by volume) Thinner/Cleaner Surface Preparation	Brush, roller or spray gun The paint is ready for use after proper stirring. If thinning is required, add 5% of Federal General Thinner MO-464 for easy application. Federal General Thinner MO-464 Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.
SHIPPING, STORAGE & PACKAGING Storage Handling Shelf life Packing Size	The product should be kept in a cool and well ventilated place protected from direct sunlight. Container must be kept tightly closed. Handle with care. Stir well before use. 12 months. 1 & 5liters
SAFETY PRECAUTION	<ul style="list-style-type: none"> * This product is flammable. Keep away from sources of ignition. Keep container tightly and keep out of reach of children. * Wear suitable personal protective clothing such as overall during painting. Ensure adequate ventilation. In case of insufficient ventilation during spraying, wear suitable respiratory equipment and eye protection goggle. Do not breathe or inhale mist. * Avoid skin and eye contact. Spillage on skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and seek medical immediately if discomfort persists.
DISCLAIMER	Federal Paint believes that the data contained herein are factual. The data are not to be taken as a warranty or representation for which Federal Paint assumes legal responsibility. We reserve the right to change the given data without notice.